

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (currently amended) A handling device for boxes and the like for repeatedly presenting the top box of a first stack (11) of boxes at a predetermined height and making it possible to remove said top box in such a way that the boxes removed from the first stack (11) gradually form a second stack (12), this device comprising:

- a first vertically movable support (9) for receiving said first stack (11);

- a second vertically movable support (10) for receiving said second stack (12); and

- means for synchronously driving the first and second supports (9, 10) so that when one goes up the other goes down and vice versa, [[]]

~~which wherein said handling device is characterized in that~~  
~~it~~ further includes a first lateral upright (2) positioned on a first side of the device and a second lateral upright (3) separate from the first upright (2) ~~each~~ and positioned on a second side of the device, opposite the first side, each of said first upright (2) and second upright (3) being provided with a slideway (7, 8), the first support (9) being mounted on the

slideway (7) of the first upright (2) and the second support (10) being mounted on the slideway (8) of the second upright (3), the device being adapted to leave free the gap between the second upright (3) and said top box of the first stack (11) at the predetermined height so that the top box of the first stack (11) is transferable directly to the second stack (12) by lateral displacement, i.e., oriented from the first side to the second side, at a more or less permanent level.

2. (currently amended) ~~Handling~~ The handling device according to claim 1, ~~characterized in that wherein~~ the supports (9, 10) are further adapted to occupy a mid-height position in which they are disposed face-to-face at more or less the same level.

3. (currently amended) ~~Handling~~ The handling device according to claim 1, ~~characterized in that wherein~~ the synchronized drive means include a cable (15) each of the ends whereof is connected to a respective one of the supports (9, 10) and which travels along a guide path (4, 5, 6) including two bottom idler pulleys (18, 19) each disposed at the base of a respective one of the lateral uprights (2, 3) and two top idler pulleys (16, 17) each disposed at the top of a respective one of the lateral uprights (2, 3), the portion (4) of the guide path situated between the bottom idler pulleys (18, 19) being

substantially horizontal and disposed under said supports (9, 10) so that the assembly formed by the two supports (9, 10) is partially surrounded by the guide path (4, 5, 6).

4. (currently amended) ~~Handling~~ The handling device according to claim 1, ~~characterized in that it~~ wherein the handling device further includes at least one motor (14) co-operating with transmission means (13) connected to the synchronized drive means.

5. (currently amended) ~~Handling~~ The handling device according to claim 4, ~~characterized in that~~ wherein said transmission means (13) connect the motor (14) to one of the supports (9, 10) so that the movement of said support (9) are driven directly by the motor (14), the movement of the other support (10) being driven by the synchronized drive means.

6. (currently amended) ~~Handling~~ The handling device according to claim 4, ~~characterized in that~~ wherein said transmission means include a transmission screw (13) adapted to be driven in rotation by the motor (14), the support (9) being connected to a threaded member meshing with the transmission screw (13).

7. (currently amended) ~~Handling~~ The handling device according to claim 3, ~~characterized in that~~ wherein at least one of the idler pulleys (16, 17, 18, 19) is mounted on a mobile shaft allowing movement of the pulley and modification of the length of the guide path (4, 5, 6).

8. (currently amended) ~~Handling~~ The handling device according to claim 7, ~~characterized in that~~ wherein one of the top idler pulleys (16, 17) is mounted so as to be mobile substantially vertically relative to the corresponding lateral upright (2, 3).

9. (currently amended) ~~Handling~~ The handling device according to claim 7, ~~characterized in that~~ wherein one of the top idler pulleys (16, 17) is connected to a threaded member meshing with an adjuster screw (20) rotatably mounted on the corresponding lateral upright (2, 3), the adjuster screw (20) being connected to drive means (21) accessible from said lateral upright (2, 3).

10. (currently amended) ~~Handling~~ The handling device according to claim 1, ~~characterized in that it~~ wherein the handling device further includes a control module (22) for the synchronized drive means and at least one sensing member (23, 24) connected to said control module (22), which is adapted to

control the synchronized drive means as a function of indications supplied by the sensing member (23, 24).

11. (currently amended) ~~Handling~~ The handling device according to claim 10, ~~characterized in that it~~ wherein the handling device includes a member (24) for sensing the height of the first stack (11).

12. (currently amended) ~~Handling~~ The handling device according to claim 10, ~~characterized in that it~~ wherein the handling device includes a member (24) for sensing the height of the second stack (12).

13. (currently amended) ~~Handling~~ The handling device according to claim 10, ~~characterized in that it~~ wherein the handling device includes at least one support sensing member (23) adapted to supply an indication to the control module (22) when the two supports (9, 10) are face-to-face.

14. (currently amended) ~~Handling~~ The handling device according to claim 1, ~~characterized in that it~~ wherein the handling device includes a safety stop member (27) mounted under at least one of said supports (9, 10) and including stop means for the supports (9, 10).

15. (currently amended) ~~Handling~~ The handling device according to claim 1, ~~characterized in that~~ wherein the synchronized drive means include two motors (28) each disposed on one of the lateral uprights (2', 3').

16. (currently amended) ~~Handling~~ The handling device according to claim 15, ~~characterized in that~~ wherein the supports (9', 10') are further adapted to occupy a high position in which they are disposed face-to-face at more or less the same level.

17. (currently amended) ~~Handling~~ The handling device according to claim 15, ~~characterized in that~~ wherein each support (9', 10') is attached to the first end of a flexible connection (29) whose second end is attached to the motor (28) so that winding in of the second end of the flexible connection (29) by the motor (28) raises the support (9', 10').

18. (currently amended) ~~Handling~~ The handling device according to claim 17, ~~characterized in that~~ wherein the motor (28) includes a winder (30) adapted to enable the second end of the flexible connection (29) to be wound up on itself by the motor (28) so that during winding the winding diameter increases.

19. (currently amended) ~~Handling~~ The handling device according to claim 18, ~~characterized in that~~ wherein the flexible

connection (29) includes a strap forming the second end of the flexible connection (29).

20. (currently amended) ~~Handling~~ The handling device according to claim 15, ~~characterized in that it~~ wherein the handling device further includes a control module (22') of the synchronized drive means and at least one sensing member (23', 24') connected to said control module (22'), which controls the synchronized drive means as a function of the indications supplied by the sensing member (23', 24').

21. (currently amended) ~~Handling~~ The handling device according to claim 20, ~~characterized in that it~~ wherein the handling device includes two sensing members (24') each disposed on one of the lateral uprights (2', 3') and each adapted to sense the height of the corresponding stack.